

I claim:

1. An airbag cushion comprising a front panel and a rear panel, wherein each of said front and rear panels has a non-circular configuration, wherein each
5 of said panels comprises generally perpendicularly arranged sets of yarns, and wherein the yarns in the front panel are at a bias to the yarns in the rear panel.

2. An airbag cushion according to Claim 1, wherein said front and rear panels comprise a fabric selected from the group consisting of woven fabrics,
10 weft inserted fabrics, weft inserted warp knit fabrics, warp or weft laid fabrics, needlepunched fabrics, and combinations thereof.

3. An airbag cushion according to Claim 1, wherein said non-circular configuration comprises a polygonal configuration with a maximum of four sides.
15

4. An airbag cushion according to Claim 1, further comprising a peripheral side panel extending between the front panel and rear panel.

5. An airbag cushion according to Claim 1, wherein said front and rear
20 panels have rounded corners.

6. An airbag cushion according to Claim 1, wherein said front and rear panels have concave sides.

25 7. An airbag cushion comprising a front panel and a rear panel, wherein each of said panels has a polygonal configuration with a maximum of four sides, wherein each of said panels is formed of at least two generally perpendicularly arranged sets of yarns, and wherein the yarns in the front panel are at a bias to the yarns in the rear panel.

30

8. An airbag cushion according to Claim 7, wherein said front and rear panels comprise a fabric selected from the group consisting of woven fabrics, weft inserted fabrics, weft inserted warp knit fabrics, warp or weft laid fabrics, needlepunched fabrics, and combinations thereof.

5

9. An airbag cushion according to Claim 7, further comprising a peripheral side panel extending between the front panel and rear panel.

10. An airbag cushion according to Claim 7, wherein said front and rear panels have rounded corners.

11. An airbag cushion according to Claim 7, wherein said front and rear panels have concave sides.

15 12. An airbag cushion comprising a front panel and a rear panel, wherein each of said front and rear panels has a geometrical configuration approximating a square, a rectangle, or a triangle, wherein said panels comprise generally perpendicularly intersecting warp and filling yarns, and wherein the yarns in the front panel are at a bias to the yarns in the rear panel.

20

13. An airbag according to Claim 12, wherein said front and rear panels have a geometrical configuration approximating a triangle.

25 14. An airbag according to Claim 12, wherein said front and rear panels have a geometrical configuration approximating a square.

15. An airbag according to Claim 12, wherein said front and rear panels have a geometrical configuration approximating a rectangle.

30 16. An airbag according to Claim 12, wherein said front and rear panels define rounded corners and generally concave sides.

17. An airbag according to Claim 12, further comprising a peripheral side panel connected to and extending between the peripheries of the front and rear panels.

5

18. An airbag nesting arrangement having a nesting efficiency of about 95% or greater.

19. A method of making an airbag comprising the steps of:
10 providing first and second fabric panels having a non-circular geometrical configuration,
orienting the panels such that at least one yarn in one of the panels is at a bias to at least one yarn in the other panel, and
securing the panels to form an airbag.

15

20. The method according to Claim 19, wherein said step of securing the panels to form an airbag comprises securing the peripheries of the first and second woven fabric panels directly to each other.

20 21. The method according to Claim 19, wherein said step of securing the panels to form an airbag comprises securing the peripheries of the first and second woven fabric panels to an intermediate side band forming panel.

22. The method according to Claim 19, wherein said panels comprise
25 generally perpendicularly intersecting lengthwise and crosswise extending yarns.

23. An airbag cushion comprising a front panel and a rear panel,
wherein each of said front and rear panels has a non-circular configuration,
wherein said front and rear panels are secured such that at least one yarn in said
30 front panel is at a bias to at least one yarn in said rear panel.